

Süther & Schön GmbH
Bonifaciusring 18
45309 Essen

Research Group for Off-Road Machines

Building IB 1/127
Universitätsstraße 150, 44801 Bochum

PROF. DR.-ING. JAN SCHOLTEN

Fon +49 (0)234/32-28723
Fax +49 (0)234/32-14161
sekretariat@lmf.rub.de

Type testing comparable to EN 13411 - 6 on belt sockets			
Part 2 (2) 6.2.4 dynamic test			
Company:		Süther & Schön GmbH	
belt			
size	name		minimum breaking force
40,0 mm	X H S		72,0 kN
belt socket:		NG 40	
	socket body	wedge	pin
item no	RG1 0040 00 000 SSN	K00 0040 00 000 SSN	B01 0040 00 000 SSN
material	G20Mn5N	AlSi9Cu3	quality 8.8
dynamic fatigue test			
no	lower load $F_u = 0,15 * F_{min}$ [kN]	upper load $F_o = 0,3 * F_{min}$ [kN]	load cycles
03 /13	10,80	21,60	75.000
result	The 2 type test samples bear the dynamic fatigue test (6.2.4) without visible cracks on body, wedge and bolt. Crack test, done by Süther & Schön GmbH, shows, that there are no cracks (enclosure).		



Dipl. Ing. A. vom Hofe

11 April 2013

(valid with signature)

ADDRESS Universitätsstraße 150 | 44801 Bochum, Germany

APPROACHE Underground: U35 | Car: A43, departure (19) Bochum Witten